



Classic Vinyls are intended for high quality interior and exterior decal applications that require durability and flexibility.

## Classic Vinyl

High strength permanent adhesive

Easy to install on flat and simple curves

Excellent whitepoint

For indoor and outdoor use

Made in the U.S.A.

Available in 4 mil. white or clear on a 90# stayflat paper liner

**Printer Compatibility:** HP Indigo, Conventional and UV Offset

## Applications

Banner Graphics

Cut Lettering

Decals

P.O.P. Signage

Bumper Stickers

Fleet Markings

In-Store Promotions



## STOCKED PRODUCTS ▶

	Finish/Color	SKU #	Size	Thickness	GSM	M Wgt	Sheets/Carton
<b>HP Indigo</b>							
	Matte White	67135	12" x 18"	4 mil	300	100	400
		67136	13" x 19"			110	
	Matte White w/ Gray Adhesive	67145	12" x 18"	4 mil	300	100	400
		67146	13" x 19"			110	
	Gloss Clear	67140	12" x 18"	4 mil	290	95	400
		67141	13" x 19"			100	
	Finish/Color	SKU #	Size	Thickness	GSM	M Wgt	Sheets/Carton
<b>Conventional &amp; UV Offset</b>							
	Matte White	67215	27" x 20"	4 mil	300	270	100
		67216	27" x 38"			520	
	Gloss Clear	67235	27" x 38"	4 mil	290	520	100



Nekoosa has 3 conveniently located converting facilities for quick shipping of custom sheets.

## TECHNICAL DATA ►

### Physical Properties

<b>Adhesive</b>	Permanent
<b>Film</b>	Flexible Vinyl
<b>Finish/Color</b>	Matte White and Gloss Clear
<b>Liner</b>	Paper
<b>Film Thickness</b>	4 mil (3.4 ± 0.2 mil)
<b>Liner Thickness</b>	90# (6.5 ± 0.2 mil)
<b>Adhesion</b>	40 ± 2 oz/in
<b>Surface Tension</b>	36 Dynes Average

### Conditions for Use

<b>Shelf Life</b>	1 year*
<b>Min. Application Temp.</b>	35° F (1.7° C)
<b>Service Temp. Range</b>	-20° F to 150° F (-28.9° F to 65.6° C)
<b>Outdoor Durability</b>	3 years**
<b>Chemical Resistance</b>	Excellent***
<b>Water Resistance</b>	Excellent
<b>Material Reuse</b>	None

\*When stored at 75° F and 50% relative humidity.

\*\*Mid-continental USA vertical exposure.

\*\*\*Excellent - commercial window cleaners.

Certified for  
HP Indigo

The information provided herein is correct to the best of Nekoosa's knowledge. No liability for any errors, facts or opinions are accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.