



NEKOOSA SPECIALTY MEDIA

Applied to Sign-Ad® Clear or Hi-Stat®, the complete opacity of this barrier film allows the printing of two-way decals for interior and exterior viewing.

Barrier Film Gloss White

This product is intended for use in creating an opaque two-way decal by laminating to a clear static cling or clear pressure sensitive film. Using barrier films avoids having to print many layers of ink on one film, which when printing with UV inks can cause the material to become extremely brittle. To accomplish two-way graphics, reverse print on clear static cling or clear film, laminate barrier film to the clear printed film, and then print on the barrier film.

Applications

Push-Pull Graphics
Window Decals
Posters
Mouse Pads
Decals

Product Information

100% opaque 2-sided window graphics
Laminate to a clear static cling or clear pressure sensitive film

Print Compatibility

UV Wide Format



TECHNICAL DATA ►

Physical Properties		2.3 mil	
Film Material	Polypropylene	Color	White
Min App Temp	+40° F / +4.4° C	Finish	Gloss
Service Temperature	-10° F to +140° F / -23.3° to +65.6° C	Weight (MSI)	.44#
Water Resistance	Good	Release Liner	40#
Chemical Resistance	Good*	Total Thickness (mil)	9.5 ± 0.5
Shelf Life	1 Year	Adhesion	40 oz ± 2
Indoor Durability	3 Years	Print Compatibility	
Outdoor Durability	1 Year	UV Wide Format	
		Roll Size	
		54" x 50 yd	•
		54" x 100 yd	•
		54" x 250 yd	•

* Resistant to most wall cleaning/household cleaning products.