

R Premask & Prespacing Tapes

HEAVY WEIGHT
PREMIUM PAPER

NEKOOSA.COM



Always lays flat, with no edge curling, wrinkling, or tunneling.

Premask is a heavyweight paper tape with low to medium tack. It covers a one piece printed vinyl graphic and protects during storage, transport, and handling.

Prespacing is a heavyweight paper tape used to mask die cut graphics. It holds cut vinyl lettering and emblems together during installation.

PREMASKS

4760 Medium/High Tack

Premask/prespacing tape for UV and solvent-based screen print inks and clear coats.

PRESPACING TAPES

4885 Extra High Tack

Prespacing tape for difficult to transfer graphics, thermal die-cut and textured window graphics.

4761RLA High Tack

Prespacing tape for Air Egress Vinyls. Designed for use with die cut and plotter cut graphics. Conform® Release Liner Adhesion prevents tunneling and edge curl.

4775RLA High Tack

Prespacing tape for small and medium die cut graphics. Compatible with most vinyl films and graphics with overlaminates. Conform® Release Liner Adhesion prevents tunneling and edge curl.

Applications

- One Piece Printed Graphics
- Wall Graphics
- Decals
- Banners

Product Information

- RLA® Release Liner Adhesion
- Lays flat with no tunneling or edge curling
- Factory cut, razor slit rolls
- No adhesive balls, gapping between layers, or crushed edges
- Tears cleanly – no stringy, legging adhesive
- Multiple roll widths available
- No adhesive build-up on stored graphics
- Works in either wet or dry applications



TECHNICAL DATA ▶

Physical Properties		4760	4885	4761RLA	4775RLA
Adhesive	Rubber-Based				
Color	Off-White/Translucent				
Tensile	297 N/100 mm (17 lb/in)				
Elongation	3-4%				
Tear Resistance	50				
Shelf Life	1 Year				
Caliper		4.3 mil	4.3 mil	4.3 mil	4.3 mil
Tack Level		Medium-High	Extra High	High	High
Adhesion to Steel*		13 - 15 oz N/100 mm	20+ oz N/100 mm	14 - 17 oz N/100 mm	15-18 oz N/100 mm
Roll Size					
24"		•		•	•
36"		•		•	•
48"		•	•	•	•
54"		•			

* TEST METHOD: PSTC-101

WARRANTY Tapes are only warranted to be free of defects in workmanship or materials at time of shipment. RTape will replace or credit any material deemed to be defective. No acceptance or responsibility for loss, damage, or expense, implied or otherwise, shall be assumed by the seller or manufacturer. The end user assumes all risk and liability.