Universal Carbonless I

CARBONLESS DESIGNED FOR DIGITAL DRY TONER/LASER AND OFFSET PRINTING



Universal Carbonless is engineered for short-run (<50,000 sheets) offset and quick turnaround on-demand digital dry toner/laser printers.

Universal Carbonless

Run on offset or digital dry toner/laser presses

Quick and easy variable data, numbering and barcoding with digital printing methods

Consistent crisp, dark, legible images through each ply

Thickest, stiffest sheet for best runnability

Custom sizes available - can be collated and micro perfed

Nekoosa Bucks available in select cartons of 8.5" x 11" and 11" x 17"

Printer Compatibility: Digital Dry Toner/Laser, Offset

Applications

Multipart Forms

Variable Data Forms

Barcoded Forms

Service Receipts

Repair Order Forms

Parking Tickets

Purchase Order Forms

Packing Slips

Bank Books

Medical Forms

Retail Receipts

Automotive Service Receipts

Legal Forms



Good for our forests.*
SFI-00677





800.826.4886 | sales@nekoosa.com

Universal Carbonless | carbonless designed for digital dry toner/laser and offset printing




NEKOOSA BUCKS available in each carton listed below.

Visit our website for our full carbonless listing.

	Parts	SKU#	Colors	Size & Grain	M Wgt	Sheets/Carton	Sets/Carton
Pre-Collated Reverse							
	2 R/S	50167	Canary CF White CB	8.5" x 11" GL	11.0	5000	2500
		50170		11" x 17" GL	22.0	2500	1250
	3 REV	50171	Pink CF Canary CFB White CB	8.5" x 11" GL	11.2	5000	1670
		50197		11" x 17" GL	22.3	2500	835
4 REV		50175	Goldenrod CF Pink CFB Canary CFB White CB	8.5" x 11" GL	11.1	5000	1250
	REV	50220		11" x 17" GL	22.3	2500	625

	Parts	SKU#	Colors	Size & Grain	M Wgt	Sheets/Carton	Sets/Carton
Pre-Collated Straight							
	3 STR 4 STR	50172	White CB Canary CFB Pink CF	8.5" x 11" GL	11.2	5000	1670
		50174		11" x 17" GL	22.3	2500	835
		50176	White CB Canary CFB	8.5" x 11" GL	11.1	5000	1250
		50244	Pink CFB Goldenrod CF	11" x 17" GL	22.3	2500	625

GL=Grain Long GS=Grain Short



Microfilming

Universal Carbonless images reproduce very well on microfilms and on most copying equipment. Equipment employing an infrared process or diazo. Where a translucent original is necessary, will not produce acceptable copies from carbonless paper.

Fan-Out Padding

This product is designed for use with Nekoosa Coated Products' Fan-Out Padding Adhesive to provided fan-apart form sets. A CB sheet in the top position and a CF sheet in the bottom position are required for proper fan out. This product is designed to repel the adhesive at the front of the CB and back of the CF sheet. This allows production forms sets when the stock is fanned at the corners.



TECHNICAL DATA

		СВ	CFB	CF	
Physical Properties					
Basis Weight (Lbs/500-17" x22")	T-410	22	23	22	
Basis Weight (g/m2)	T-410	83	86	83	
Thickness	T-411	4.5 mil	4.2 mil	4.1 mil	
Brightness (White only)	T-452	92	-	-	
Opacity	T-425	88.1%	-	-	
Image Color	NCP Test	Black	-	-	
Odor	NCP Test	Very Slight Odor	-	-	

Test methods prefixed with a "T" are established by Technical Association of the Pulp and Paper Industry.

Conditions For Use		
	Shelf Life*	2 years

*When kept in a copy room condition and properly resealed in original packing when not in use.

IF YOUR MACH	IINE DOES THIS	THIS IS WHAT YOU NEED		
Print This Side Of The Sheet	Delivers The Print This Way	This Collation	Loaded With The Arrows (print side)	
Тор	Print Side Up	Reverse	Up	
Тор	Print Side Down	Straight	Up	
Bottom	Print Side Up	Straight	Down	
Bottom	Print Side Down	Reverse	Down	

Speed of Image Formation

The image of Universal Carbonless paper is immediately legible. The image will continue to darken over a short period of time and will be most apparent in handwritten forms. Extreme cold temperatures will slow down the speed of the image formation and conversely, higher temperature will increase the reaction time.

Pressure Required to Image

Because of the difference in individual requirements, the wide range of pressure exerted by various printers or writing pressure associated with hand entry, users should conduct test simulating actual usage conditions for assuring satisfactory performance in specific applications.

Image Test

Make a small firm mark on the first completed form set. Check each ply for presence of carbonless image. This will indicate whether or not the printing/copying is being performed on proper side of the paper.

Press and Ink

Universal Carbonless paper may also be printed on wet offset, dry offset and letterpress equipment. Standard low-tack inks give good performance. If utilizing UV offset inks, set UV lamps to lowest setting that will cure the inks. UV light exposure will cause the premature development of the imaging inks with enough intensity and time of exposure.

Pre-collated Universal Carbonless paper is specifically designed for use with machines using toner heart fusing systems and delivering sheets into a receiving tray.

Conditioning and Handling

As with most paper grades, Universal Carbonless paper should be acclimated to copy room conditions before printing. Keep paper stored in original protective packaging until needed. Unused paper should be resealed in the original wrapper and stored in a controlled environment. Handle paper with minimal pressure to avoid inadvertently marking or scuffing of the paper.

The information provided herein is correct to the best of Nekoosa's knowledge, however, should not be construed as specifications. No liability for any errors, facts or opinions are accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

