

PRESSURE SENSITIVE TEXTURED VINYL



One product, endless applications. Create floor, wall and window graphics with one universal media ... Trifecta®.

Trifecta™

6 mil semi-rigid matte white textured facestock rated for <5 years of outdoor use High opacity film with an excellent white point

Universal removable adhesive that will cleanly remove from indoor and outdoor applications for <6 months

Stable 90# layflat polycoated paper liner for ease of printing and installation

Print Compatibility: Wide Format (Solvent, Eco-Solvent, Latex and UV), UV Offset and Screen

When to use Trifecta

One-Step Floor Graphics - Create UL 410 slip resistant floor graphics in one easy step ... no overlaminate required. Easy to install and remove. Trifecta™ is suitable for indoor short term floor graphics (<6 months). *Not intended for outdoor floor graphic applications.

Wall Graphics - Hassle free textured wall decals - peel, stick, done. No need for tapes, tacks or nails and will remove cleanly from painted dry wall.

Window Graphics - Enhance the look of standard window graphics with a dimensional, textured finish. Perfect for short term decorative window decals smaller than 2' x 2'.

Applications

One-Step Floor Graphics

Wall Graphics

Window Signage

Social Distancing Floor Graphics

Counter Mats

Posters

Wall Décor

Wayward Signage

Directional Arrows

One-Way Window Graphics

Floor Advertisement

Point-of-Purchase Signage









TRIFECTA







STOCKED PRODUCTS ▶

	Finish/Color	SKU#	Size	Thickness	Adhesive	Liner	Rolls/Carton
Wide Format							
	Textured Matte White	SPMTRI54100	54" x 100 ft	6 mil	Universal Removable	90# Layflat	1

Easy to apply and remove from these surfaces:





TRIFECTA







CUSTOM SIZE OFFERING ▶

	Finish/Color	SKU#	Size (width)	Film Thickness	Adhesive	Liner	Wgt/MSI
Non Top Coated - UV Offset, Screen							
	Textured Matte White	TRIFECTA	54"	6 mil	Universal Removable	90# Layflat	.64#

 $\textbf{Custom Size Offering:} Custom \ converted \ sheet \ and \ roll \ options \ available \ to \ meet \ your \ specific \ requirements.$









TECHNICAL DATA

			Trifecta™	
Physical Properties				
	Finish		Textured	
	Color	White		
	Adhesive	Universal Removable - UR1		
	Film	Calendered Vinyl		
	Liner		90# Layflat	
	Opacity Gloss Level		95% Minimum	
			2% Typical	
		Film	6 ± 0.2 mil	
	Thickness	Film w/ Adhesive	6.7± 0.2 mil	
		Total Thickness	13.2±0.4 mil	
	Adhesion	SS 15 min Room Temp Dwell	16-20 oz/in	
		SS 24 hr Room Temp Dwell	23-27 oz/in	
	Weight	Film w/ Adhesive	265-270 gsm	
	MeiRiir	Total w/ Liner	410-420 gsm	
	Slip Resistant Certification	UL 410		

Conditions for Use					
	Shelf Life	1 year			
	Clean Removability	Up to 6 months			
	Outdoor Durability	Up to 5 years			
	Min Application Temp	40° F (4° C)			
	Service Temp Range	-20° to 150° F (-29° to 66° C)			
	Solvent Resistance	Good*			
	Water Resistance	Excellent			

CPSIA Compliant

*Good for most petroleum solvents and lower aliphatic alcohols. For ultimate solvent resistance, edge sealing is recommended.

The information provided herein is correct to the best of Nekoosa's knowledge, however, should not be construed as specifications. No liability for any errors, facts or opinions are accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.

