



ELECTRICALLY CHARGED
POLYPROPYLENE



ClingZ® is an adhesive-free electrically charged film that adheres to any dry interior surface and is effortless to reposition.

ClingZ

Ideal for temporary indoor marketing applications

Effortless to apply, remove and reposition to any dry interior surface

Adhesive free – no glue, tape, tacks or pins required

Recyclable, chemically inert, PVC-Free and phthalate-free

Can be die cut, kiss cut and plotter cut

Available in white and clear

Four grades engineered specifically for offset (ClingZ® Standard Offset and ClingZ® Versaliner), HP Indigo and UV wide format

Print Compatibility: Offset (Conventional and UV), HP Indigo and UV Wide Format*

Easy to apply and remove from these surfaces:



ClingZ is not to be confused with Static Cling Vinyl. Static Cling Vinyls cling to glass because of their high plasticizer content. **They do NOT cling by static.** Only ClingZ gets its cling properties due to having an embedded static charge.

Applications

- Screen Safe Labels
- In-Store Promotional Signage
- Large Format Graphics
- Tileable Murals
- P.O.P. Signage
- Reverse Sided Graphics
- Trade Show & Event Signage
- Window Graphics
- Holiday Décor & Decals
- Guerrilla Marketing

Certified for
HP Indigo



ELECTRICALLY CHARGED
POLYPROPYLENE



STOCKED PRODUCTS ▶

	Color	SKU #	Size	GSM	M Wgt	Qty/Unit	
ClingZ Standard Offset							
White		71100	19" x 25"	240	162.2	2000/skid	
		71101	23" x 35"		274.8	2000/skid	
		71102	28" x 40"		382.4	2000/skid	
		71105	19" x 25"		162.2	200/carton	
		71106	23" x 35"		274.8	200/carton	
		71107	28" x 40"		382.4	200/carton	
	Clear		71110		19" x 25"	164.2	2000/skid
			71111		23" x 35"	278.3	2000/skid
			71112		28" x 40"	387.2	2000/skid
			71115		19" x 25"	164.2	200/carton
		71116	23" x 35"	278.3	200/carton		
		71117	28" x 40"	387.2	200/carton		
ClingZ Versaliner Offset*							
White		71200	20" x 28"	243	193.6	2000/skid	
		71201	28" x 40"		387.2	2000/skid	
		71205	20" x 28"		193.6	250/carton	
		71206	28" x 40"		387.2	250/carton	
	Clear		71210		20" x 28"	246	196.0
		71211	28" x 40"	392.0	2000/skid		
		71215	20" x 28"	196.0	250/carton		
		71216	28" x 40"	392.0	250/carton		
ClingZ HP Indigo							
White		71300	12" x 18"	269	82.6	500/carton	
		71301	13" x 19"		94.5	500/carton	
		71310	20.5" x 29.5"		231.4	1200/skid	
		71312	20.5" x 29.5"		231.4	300/carton	
Clear		71305	12" x 18"	261	80.2	500/carton	
		71306	13" x 19"		91.7	500/carton	
		71311	20.5" x 29.5"		224.5	1200/skid	
		71313	20.5" x 29.5"		224.5	300/carton	
ClingZ Wide Format							
	White	71514	54" x 75'	161	12	1/Roll	
	Clear	71515	54" x 75'	155	12	1/Roll	

*Select ClingZ Versaliner if extra finishing like die or kiss cutting is required.



ELECTRICALLY CHARGED
POLYPROPYLENE

TECHNICAL DATA ▶

Physical Properties			Offset	Versaliner	HP Indigo	UV Wide Format	
Film	Polypropylene	Liner	10 pt paper	10 pt paper	10 pt paper	PET	
Color	White and Clear	Thickness	Film	2 mil (50.8 μ)	2 mil (50.8 μ)	2 mil (50.8 μ)	2 mil (50.8 μ)
			Liner	10 mil (254 μ)	10 mil (254 μ)	10 mil (254 μ)	3 mil (76.2 μ)
			Film + Liner	12 mil (304.8 μ)	12 mil (304.8 μ)	12 mil (304.8 μ)	5 mil (127 μ)

Conditions for Use			Offset	Versaliner	HP Indigo	UV Wide Format
Shelf Life	1 year	Application Time	6 months	6 months	3 months	3 months
Min. Application Temp.	32° F (0° C)					
Service Temp. Range	0° F to 105° F (-17.8° C to 40.5° C)					
Outdoor Durability	None					

General Printing and Designing Guidelines:

- Design for finished sizes of at least 3"x5" (8x12 cm).
- Convert PMS spot colors to CMYK process-ink builds.
- Stay within a total area coverage (TAC) of 220% in color build with a line screen of 150-175, and reduce screen values by using UCR or GCR.
- Avoid heavy deposits of ink near the edge to avoid curling.
- Right reading or reverse printing is possible.
- A 1" (2.5 cm) unprinted border will enhance the performance of the application.
- Add no more than 2 hits of opaque white before 4-color process when printing on clear film.
- Add white after the 4-color process if printing verse.
- This product is not suitable for screen printing or any type of coating, including varnishes or aqueous and UV coatings.

Storing:

- Store in the original packaging at room temperature 65° F-80° F (18° C-27° C) with relative humidity of 25-50%.
- Acclimate the material to press room temperature for 24 hours prior to printing.
- Remove material from plastic bag right before the loading the press.
- Reseal unused materials in the original plastic bag.
- Paper liner is moisture sensitive and can curl if improperly stored.
- Unprinted ClingZ can be stored for up to one year.

Additional Information:

- ClingZ is not to be confused with static cling vinyl. Static cling vinyls adhere to glass because of their high plasticizer content. They do not cling by static. Only ClingZ gets its cling properties due to having an embedded static charge.



HP CERTIFIED:
ClingZ for HP Indigo Clear 5000, 5500, 5600 multi-shot, 7000, 7500, 7600, 7800 and 7900
ClingZ for HP Indigo White 5000, 5500, 5600 multi-shot, 7000, 7500, 7600, 7800 and 7900

The information provided herein is correct to the best of Nekoosa's knowledge. No liability for any errors, facts or opinions are accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.



800.826.4886 | sales@nekoosa.com

NEKOOSA.COM

02.10.23