



Metalized polyester films used in the production of high quality applications that require metallic luster, durability and dimensional stability.

PolyEfx[®]

Dimensionally stable films for high quality die cutting applications

2 mil metalized polyester facestock

High peel, high tack permanent adhesive

90# layflat paper liner

Not recommended for outdoor use

Print Compatibility: UV Wide Format, UV and Conventional Offset/Litho and Screen

Applications

- Cut Lettering
- Decals
- Point-of-Purchase
- Signage
- Holiday Décor
- Fleet Markings
- Decorative In-Store
- Displays
- Seasonal Signage
- Decorative Labels
- Trade Show Graphics
- Event Signage
- Banner Graphics
- Name Plates
- Bumper Stickers
- In-Store Promotions



POLYEFX®

CUT LETTERING
SIGN POLYESTER



STOCKED PRODUCTS ▶

Color	SKU #	Size
Indoor Metalized Polyester		
Bright Silver	CMS2450A	24" x 50 yd
	CMS3050A	30" x 50 yd
	CMS4850A	48" x 50 yd
	CMS5450A	54" x 50 yd
Brushed Silver	CMBS2450A	24" x 50 yd
	CMBS3050A	30" x 50 yd
	CMBS4850A	48" x 50 yd
	CMBS5450A	54" x 50 yd
Bright Gold	CMG2450A	24" x 50 yd
	CMG3050A	30" x 50 yd
	CMG4850A	48" x 50 yd
	CMG5450A	54" x 50 yd

CUSTOM SIZE OFFERING ▶

Finish/Color	SKU #	Size (width)	Thickness	Adhesive	Liner	Wgt/MSI
Indoor Metalized Polyester						
Bright Silver	CM200S	54"	2 mil	High-Peel, High-Tack Permanent	90# Layflat	.44#
Brushed Silver	CM200BS	54"	2 mil	High-Peel, High-Tack Permanent	90# Layflat	.44#
Bright Gold	CM200G	54"	2 mil	High-Peel, High-Tack Permanent	90# Layflat	.44#

Custom Size Offering: Custom converted sheet and roll options available to meet your specific requirements.

TECHNICAL DATA ▶

Physical Properties		Metalized Polyester
Finish		Metalized
Color		Various - See Chart
Adhesive		Permanent - P82
Film		Polyester
Liner		90# Layflat
Opacity		98% minimum
Gloss Level		Bright/Brushed
Thickness	Film	2.0 ± 0.2 mil
	Film + Adhesive	2.9 ± 0.2 mil
	Total Thickness	9.4 ± 0.4 mil
Adhesion*	SS 15 min room temp dwell	25 oz/in minimum
	SS 24-hr room temp dwell	80 oz/n minimum
Weight	Film + Adhesive	90-100 gsm
	Total w/ Liner	240-250 gsm
Printability		UV Wide Format, Screen, Offset and Litho

Conditions for Use		Metalized Polyester
Shelf Life*		1 year
Outdoor Durability**		Not recommended
Min Application Temp		40°F (4°C)
Service Temp Range		-20° to 275° F (-29° to 135° C)
Solvent Resistance***		Good
Water Resistance		Excellent

Store open rolls horizontally, suspended through the core with suitable bar. Do not store vertically on end; this will cause cracking of the sheeting light source.

*When stored at 75° F and 50% relative humidity

**Mid-continental U.S. vertical

***Good for most petroleum solvents and lower aliphatic alcohols. For ultimate solvent resistance, edge sealing is recommended

The information provided herein is correct to the best of Nekoosa's knowledge. No liability for any errors, facts or opinions are accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.