



ClingZ® is an adhesive-free electrically charged film that adheres to any dry interior surface and is effortless to reposition.

ClingZ

Ideal for temporary indoor marketing applications

Effortless to apply, remove, and reposition to any dry interior surface

Adhesive free - no glue, tape, tacks or pins required

Chemically inert, PVC-free, and phthalate-free

Can be die cut, kiss cut, and plotter cut

Print Compatibility: Offset (Conventional and UV), HP Indigo and UV Wide Format*



This logo represents Nekoosa's commitment to offering sustainable alternatives to traditional PVC materials. 100% of this product line is PVC-Free.

Easy to apply and remove from these surfaces:

PAINTED WALLS	WALLPAPER	WOOD PANELING BRICK			
CONCRETE	POLISHED STONE	STAINLESS	GLASS		



Applications

Screen Safe Labels

In-Store Promotional Signage

Large Format Graphics

Tileable Murals

P.O.P. Signage

Reverse Sided Graphics

Trade Show & Event Signage

Window Graphics

Holiday Décor & Decals

Guerrilla Marketing

Certified for **HP Indigo**











STOCKED PRODUCTS ▶

	Color	SKU#	Size	GSM	M Wgt	Qty/Unit			
ClingZ Standard Offset									
		3 71100	19" x 25"	240	162.2	2000/skid			
		3 71101	23" x 35"		274.8	2000/skid			
	White	3 71102	28" x 40"		382.4	2000/skid			
	wnite	3 71105	19" x 25"		162.2	200/carton			
		3 71106	23" x 35"		274.8	200/carton			
		3 71107	28" x 40"		382.4	200/carton			

	Color	SKU#	Size	GSM	M Wgt	Qty/Unit		
ClingZ Versaliner Offset*								
	White	3 71200	20" x 28"	243	193.6	2000/skid		
		3 71201	28" x 40"		387.2	2000/skid		
		3 71205	20" x 28"		193.6	250/carton		
		3 71206	28" x 40"		387.2	250/carton		

*Select ClingZ Versaliner if extra finishing like die or kiss cutting is required.

	Color	SKU#	Size	GSM	M Wgt	Qty/Unit		
ClingZ HP Indigo								
	White	3 71300	12" x 18"	269	82.6	500/carton		
		3 71301	13" x 19"		94.5	500/carton		
		> 71310	20.5" x 29.5"		231.4	1200/skid		
		3 71312	20.5" x 29.5"		231.4	300/carton		

	Color	SKU#	Size	GSM	Roll Wgt	Qty/Unit	
ClingZ Wide Format							
	White	≫ 71514 ●	54" x 75'	161	12	1/Roll	





HP CERTIFIED:

 $\textbf{ClingZ for HP Indigo}\ 5000, 5500, 5600\ multi-shot, 7000, 7500, 7600, 7800, and\ 7900$







TECHNICAL DATA ▶

		•		Offset	Versaliner	HP Indigo	UV Wide Format		
Physical Properties									
Film	Polypropylene	Liner		10 pt paper	10 pt paper	10 pt paper	PET		
	White	ору.ее	Film	2 mil (50.8 μ)	2 mil (50.8 μ)	2 mil (50.8 μ)	2 mil (50.8 μ)		
Color		Thickness	Liner	10 mil (254 μ)	10 mil (254 μ)	10 mil (254 μ)	3 mil (76.2 μ)		
			Film + Liner	12 mil (304.8 μ)	12 mil (304.8 μ)	12 mil (304.8 μ)	5 mil (127 μ)		

			Offset	Versaliner	> HP Indigo	> UV Wide Format
Conditions for Use	е					
Shelf Life	1 vear	Application Time	6 months	6 months	3 months	3 months

Min. Application Temp. 32° F (0° C)

Service Temp. Range 0° F to 105° F (-17.8° C to 40.5° C)

Outdoor Durability None

General Printing and Designing Guidelines:

- · Design for finished sizes of at least 3"x5" (8x12 cm).
- · Convert PMS spot colors to CMYK process-ink builds.
- · Stay within a total area coverage (TAC) of 220% in color build with a line screen of 150-175, and reduce screen values by using UCR or GCR.
- · Avoid heavy deposits of ink near the edge to avoid curling.
- · Right reading or reverse printing is possible.
- · A 1" (2.5 cm) unprinted border will enhance the performance of the application.
- · This product is not suitable for screen printing or any type of coating, including varnishes or aqueous and UV coatings.

Storing:

- · Store in the original packaging at room temperature 65° F-80° F (18° C-27° C) with relative humidity of 25-50%.
- · Acclimate the material to press room temperature for 24 hours prior to printing.
- · Remove material from plastic bag right before the loading the press.
- · Reseal unused materials in the original plastic bag.
- · Paper liner is moisture sensitive and can curl if improperly stored.
- · Unprinted ClingZ can be stored for up to one year.

Additional Information:

- · ClingZ is not to be confused with static cling vinyl. Static cling vinyls adhere to glass because of their high plasticizer content. They do not cling by static. Only ClingZ gets its cling properties due to having an embedded static charge.
- · ClingZ is recyclable as a #5 plastic. Confirm specific recycling guidelines with your local municipality.



HP CERTIFIED:

ClingZ for HP Indigo 5000, 5500, 5600 multi-shot, 7000, 7500, 7600, 7800 and 7900

The information provided herein is correct to the best of Nekoosa's knowledge. No liability for any errors, facts or opinions are accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.



= PVC-Free