



NEXTBOND®

# HIGH-BOND OPAQUE

OPAQUE  
PRINT MEDIA



Built to perform - durable, reliable, and ready for any surface in any season.

## High-Bond Opaque (HBO)

**Unmatched Opacity** - >99.5% opacity provides full coverage without sacrificing adhesive performance through gray pigment contamination

**True Block-Out Solution** - Opaque polymeric vinyl completely conceals existing graphics without ghosting or show-through, making it ideal for graphic replacement and block out applications

**Ultimate Adhesion** - Double layer of NextBond® UV-cured, high bond durable adhesive ensures a secure, long lasting hold on low surface energy plastics, concrete, brick, and more - even in extreme weather conditions

**Extreme Durability** - Withstands intense environmental conditions like heat, freezing cold, humidity, direct sunlight, rain, snow, and more

**Long Lasting Performance** - Rated for 5 years of outdoor use with built-in UV inhibitors to prevent fading



**Cold-Weather Installation** - Designed for year-round application, NextBond® High-Bond Opaque can be installed in temperatures as low as -10°F, making it an ideal solution for cold-weather environments

**Pristine Print Quality** - Specially engineered printing surface resists plasticizer migration and blooming, ensuring crisp, vibrant wide-format prints

**Conformable** - Flexible film conforms to uneven, contoured, and textured applications for a seamless, professional finish.

**Printer Compatibility:** Wide Format  
(Eco-Solvent/Solvent, Latex, UV), Offset (UV), Screen

SCAN HERE FOR  
FREE SAMPLES ▶



## Applications

- Opaque Signage
- Cover-Up Graphics
- Long-Term Graphics
- Temporary Signage
- Decals
- Textured Surfaces
- Flat & Slightly Curved Surfaces
- Indoor & Outdoor Signage
- Plywood Renovation Barricades
- Temporary Construction Walls
- Tiled/Panel Graphics
- Plotted Graphics



NEXTBOND®

# HIGH-BOND OPAQUE

OPAQUE  
PRINT MEDIA



## STANDARD SIZES ▶

Finish/Color	SKU #	Roll Size	Film Thickness	Adhesive	Liner	Rolls/Carton
<b>High-Bond Opaque</b>						
Opaque Matte White	UVSPM400FWOP-HBP5450	54" x 50 yd	3.2 mil	NextBond® High-Bond Permanent	90# Layflat	1
	UVSPM400FWOP-HBR5450	54" x 50 yd	3.2 mil	NextBond® High-Bond High-Peel Removable	90# Layflat	1
	UVSPE400FWOP-HBP5450	54" x 50 yd	3.2 mil	NextBond® High-Bond Permanent	90# Layflat Air-Egress	1
	UVSPE400FWOP-HBR5450	54" x 50 yd	3.2 mil	NextBond® High-Bond High-Peel Removable	90# Layflat Air-Egress	1



**NEKOOSA BUCKS**

available in select rolls listed above.

\*Print Compatibility - Wide Format (Eco-Solvent/Solvent, Latex, UV)

\*Each product listed above is offered in custom sizes. Please contact us for more details.

Easy to apply and remove from these surfaces and many more...



\*We recommend testing NextBond on your specific application surface to ensure compatibility.



800.826.4886 | cs@nekoosa.com

NEKOOSA.COM

04.17.25



NEXTBOND®

# HIGH-BOND OPAQUE

OPAQUE  
PRINT MEDIA

## TECHNICAL DATA ▶

High-Bond Opaque ▶		UVSPM400FWOP-HBP	UVSPM400FWOP-HBR	UVSPE400FWOP-HBP	UVSPE400FWOP-HBR
<b>Physical Properties &amp; Conditions for Use</b>					
<b>Film</b>	Type	Vinyl	Vinyl	Vinyl	Vinyl
	Finish	Matte	Matte	Matte	Matte
	Color	White	White	White	White
	Opacity	>99.5%	>99.5%	>99.5%	>99.5%
	Gloss Level	<20% Maximum	<20% Maximum	<20% Maximum	<20% Maximum
<b>Outdoor Durability Rating (Film)</b>		5 Years	5 Years	5 Years	5 Years
<b>Adhesive</b>	Strength	High-Bond Permanent, 2.0 mil	High-Bond High-Peel Removable, 2.0 mil	High-Bond Permanent, 2.0 mil	High-Bond High-Peel Removable, 2.0 mil
	Color	Clear	Clear	Clear	Clear
	Outdoor Durability Rating (Adhesive)	10 Years	10 Years	10 Years	10 Years
<b>Liner</b>		90# Layflat	90# Layflat	90# Layflat Air-Egress	90# Layflat Air-Egress
<b>Thickness</b>	Film	3.2 ± 0.2 mil	3.2 ± 0.2 mil	3.2 ± 0.2 mil	3.2 ± 0.2 mil
	Film w/ Adhesive	5.2 ± 0.5 mil	5.2 ± 0.5 mil	5.2 ± 0.5 mil	5.2 ± 0.5 mil
	Total Thickness	11.8 ± 1.2 mil	11.8 ± 1.2 mil	12.8 +/- 1.3 mil	12.8 +/- 1.3 mil
<b>Adhesion</b>	SS 15 min Room Temp Dwell	100 oz/in typical	30 oz/in typical	75 oz/in typical	20 oz/in typical
	SS 24 hr Room Temp Dwell	140 oz/in typical	40 oz/in typical	135 oz/in typical	30 oz/in typical
<b>Weight</b>	Film w/ Adhesive	153 to 180 gsm	153 to 180gsm	153 to 180 gsm	153 to 180 gsm
	Total w/ Liner	294 to 331 gsm	294 to 331 gsm	319 to 356 gsm	319 to 356 gsm
<b>Repositionable</b>		No	During Installation	No	During Installation
<b>Minimum Application Temperature</b>		-10° F (-23° C)	10° F (-12° C)	-10° F (-23° C)	10° F (-12° C)
<b>Service Temperature Range</b>		-45° to 210° F (-43° to 99° C)	-45° to 180° F (-43° to 82° C)	-45° to 210° F (-43° to 99° C)	-45° to 180° F (-43° to 82° C)
<b>Removal Temperature</b>		-	>40° F	-	>40° F

### Additional Information:

- Shelf Life = 1 Year
- Storage Conditions = 60°-75° F (45-65% relative humidity)
- Each NextBond® product has excellent resistance to water, solvents, and harsh environmental conditions.

The information provided herein is correct to the best of Nekoosa's knowledge, however, should not be construed as specifications. No liability for any errors, facts or opinions are accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.