



ApliTape™ is the original RTape application tape in an affordably priced, factory cut, razor slit roll.

ApliTape

Works in either wet or dry applications

Available in standard and heavyweight paper grades, in a variety of tack levels

No adhesive build-up on stored graphics

No adhesive balls, gapping between layers or crushed edges

4000 Low Tack

- Standard grade saturated paper premask
- Low tack rubber adhesive

4050 Medium Tack

- Standard grade saturated paper application tape
- Medium tack rubber adhesive

4075 High Tack

- Standard grade saturated paper application tape
- High tack rubber adhesive

Applications

General Purpose Sign Applications

Screen Printing

Digital Printing



STOCKED PRODUCTS ▶

Tack Level	Size	SKU #	Rolls/Carton	Cartons/Pit
4000				
Low	24" x 100 yd	1400700	2	42
	48" x 100 yd	1401420	1	42

Tack Level	Size	SKU #	Rolls/Carton	Cartons/Pit
4050				
Medium	16" x 100 yd	1411240	4	27
	18" x 100 yd	1411400	2	42
	20" x 100 yd	1411520	2	42
	24" x 100 yd	1411720	2	42
	30" x 100 yd	1412000	1	42
	36" x 100 yd	1412280	1	42
	48" x 100 yd	1412800	1	42
	54" x 100 yd	1413870	1	42
	60" x 100 yd	1415055	1	42

Tack Level	Size	SKU #	Rolls/Carton	Cartons/Pit
4075				
High	1.25" x 100 yd	1470020	36	27
	2.25" x 100 yd	1470102	20	27
	3.25" x 100 yd	1470184	12	27
	4.25" x 100 yd	1470262	12	27
	6.5" x 100 yd	1470458	8	27
	8.5" x 100 yd	1470598	4	27
	10.5" x 100 yd	1470758	4	27
	12" x 100 yd	1470880	4	27
	14" x 100 yd	1471040	4	27
	15" x 100 yd	1471122	4	27
	16" x 100 yd	1471202	4	27
	18" x 100 yd	1471360	2	42
	20" x 100 yd	1471520	2	42
	24" x 100 yd	1471840	2	42
	30" x 100 yd	1472320	1	42
	36" x 100 yd	1472800	1	42
	48" x 100 yd	1473760	1	42
	54" x 100 yd	1474232	1	42
	60" x 100 yd	1474720	1	42



TECHNICAL DATA ▶

Physical Properties & Conditions For Use			4000	4050	4075	
Adhesive	Rubber-based	Caliper	Facestock	4.0 - 4.5 mil (100-113 μ)	4.0 - 4.5 mil (100-113 μ)	4.0 - 4.5 mil (100-113 μ)
Color	White/Translucent		Facestock + Adhesive	5.0 - 5.5 mil (125 - 138μ)	5.0 - 5.5 mil (125 - 138μ)	5.0 - 5.5 mil (125 - 138μ)
Tensile	297 N/100 mm (17lb/in)	Tack Level	Low	Medium	High	
Elongation	3-4%	Adhesion	Stainless Steel*	7-9 N/100 mm (6-8oz)	13-15 N/100 mm (12-14oz)	18-20 N/100 mm (16-18oz)
Tear Resistance	50 grams					
Shelf Life	1 year					

Additional Information:

- Removes easily following graphics application.
- If adhesive touches adhesive, perform pulls apart easily with no adhesive delamination.
- Works well in either wet or dry applications with no adhesive transfer.

WARRANTY Tapes are only warranted to be free of defects in workmanship or materials at time of shipment. Nekoosa will replace or credit any material deemed to be defective. No acceptance or responsibility for loss, damage, or expense, implied or otherwise, shall be assumed by the seller or manufacturer. The end user assumes all risk and liability.

The information provided herein is correct to the best of Nekoosa's knowledge. No liability for any errors, facts or opinions are accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.