



Conform<sup>®</sup> is the original application tape with Release Liner Adhesion (RLA<sup>®</sup>) that lays flat without tunneling or edge curling.

## Conform

Standard weight paper application tape that works in either wet or dry applications

Factory cut, razor slit rolls

No adhesive balls, gapping between layers or crushed edges

Tears cleanly – no stringy, legging adhesive

Multiple roll widths available

No adhesive build-up on stored graphics

### 4075RLA High Tack

- High tack rubber adhesive
- Small to mid-sized pre-spaced vinyls and printed graphics

### 4076RLA Very High Tack

- Coated with a slightly higher tack rubber adhesive
- Small-sized cut graphics and hard-to-lift vinyls

### 4050RLA Medium Tack

- Medium tack rubber adhesive
- Medium to large-sized, pre-spaced vinyl and printed graphics

### 4078RLA Medium High Tack

- Medium tack rubber adhesive
- Wall graphics, textured and frosted vinyl

## Applications

General Purpose Sign Applications

Decals

Banners

Wall Graphics

# CONFORM® | APPLICATION TAPE WITH RLA




## STOCKED PRODUCTS ▶

Tack Level	Size	SKU #	Rolls/Carton	Cartons/Plt
<b>4050 RLA</b>				
Medium w/ RLA	2.25" x 100 yd	1420150	20	27
	3.25" x 100 yd	1420190	12	27
	4.25" x 100 yd	1420230	12	27
	6.50" x 100 yd	1420320	8	27
	8.50" x 100 yd	1420400	4	27
	10.50" x 100 yd	1420480	4	27
	12" x 100 yd	1420540	4	27
	14" x 100 yd	1420620	4	27
	15" x 100 yd	1420660	4	27
	16" x 100 yd	1420700	4	27
	18" x 100 yd	1420756	2	42
	20" x 100 yd	1420860	2	42
	24" x 100 yd	1421020	2	42
	30" x 100 yd	1421260	1	42
	36" x 100 yd	1421500	1	42
48" x 100 yd	1422016	1	42	
54" x 100 yd	1422034	1	42	
60" x 100 yd	1422066	1	42	

Tack Level	Size	SKU #	Rolls/Carton	Cartons/Plt
<b>4075 RLA</b>				
Medium w/ RLA	1.25" x 100 yd	1740010	36	27
	2.25" x 100 yd	1740050	20	27
	3.25" x 100 yd	1740090	12	27
	4.25" x 100 yd	1740130	12	27
	5.25" x 100 yd	1740170	8	27
	6.50" x 100 yd	1740220	8	27
	8.50" x 100 yd	1740300	4	27
	10.50" x 100 yd	1740380	4	27
	12" x 100 yd	1740440	4	27
	14" x 100 yd	1740520	4	27
	15" x 100 yd	1740560	4	27
	16" x 100 yd	1740600	4	27
	18" x 100 yd	1740680	2	42
	20" x 100 yd	1740760	2	42
	24" x 100 yd	1740920	2	42
	30" x 100 yd	1741160	1	42
	36" x 100 yd	1741400	1	42
	48" x 100 yd	1741880	1	42
54" x 100 yd	1742122	1	42	
60" x 100 yd	1742362	1	42	

Tack Level	Size	SKU #	Rolls/Carton	Cartons/Plt
<b>4076 RLA</b>				
Extra High w/ RLA	6.5" x 100 yd	1750688	8	27
	10.5" x 100 yd	1750758	4	27
	12" x 100 yd	1750790	4	27
	14" x 100 yd	1750808	4	27
	15" x 100 yd	1750848	4	27
	16" x 100 yd	1750828	4	27
	18" x 100 yd	1751080	2	27
	20" x 100 yd	1751120	2	42
	24" x 100 yd	1751208	2	42
	30" x 100 yd	1751280	1	42
36" x 100 yd	1751400	1	42	
48" x 100 yd	1751880	1	42	

Tack Level	Size	SKU #	Rolls/Carton	Cartons/Plt
<b>4078 RLA</b>				
Medium w/ RLA	6.5" x 100 yd	1776494	8	27
	12" x 100 yd	1776626	4	27
	14" x 100 yd	1776674	4	27
	24" x 100 yd	1776910	2	42
	30" x 100 yd	1777058	1	42
48" x 100 yd	1777470	1	42	



**TECHNICAL DATA** ▶

Physical Properties & Conditions for Use				4078RLA	4050RLA	4075RLA	4076RLA
<b>Adhesive</b>	Rubber-based	<b>Caliper</b>	Facestock	3.0 mil	3.0 mil	3.0 mil	3.0 mil
<b>Color</b>	Off White/Translucent		Facestock + Adhesive	4.1 mil	4.2 mil	4.2 mil	4.3 mil
<b>Tensile</b>	297 N/100 mm (17lb/in)	<b>Tack Level</b>		Medium	Medium	High	Very High
<b>Elongation</b>	3-4%						
<b>Tear Resistance</b>	50	<b>Adhesion*</b>	PSTC -101	9-11 N/100 mm (7.5-8 oz)	13-14 N/100 mm (12-14 oz)	18-20 N/100 mm (15-18 oz)	19-21 N/100 mm (17-19 oz)
<b>Shelf Life</b>	1 year						

\* Adhesion to steel

**WARRANTY** Tapes are only warranted to be free of defects in workmanship or materials at time of shipment. Nekoosa will replace or credit any material deemed to be defective. No acceptance or responsibility for loss, damage, or expense, implied or otherwise, shall be assumed by the seller or manufacturer. The end user assumes all risk and liability.

The information provided herein is correct to the best of Nekoosa's knowledge. No liability for any errors, facts or opinions are accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.