

NEKOOSA **GLASS FINISHES[®]**

Deep Etch



Light Etch

Dusted Crystal

Sand Blast

Sand Matte

Bird Safety Film



Nekoosa Glass Finishes® offers a wide range of printable window films designed to transform the appearance of interior and exterior commercial buildings for privacy and finishing purposes. Available in Deep Etch, Light Etch, Dusted Crystal, Sand Blast and Sand Matte finishes, each film offers a degree of privacy by obscuring direct visibility while allowing excellent light transmission. Each film includes a solvent-performance permanent adhesive and a PET liner for excellent printability and 7 years of outdoor durability. For detailed designs and lettering, these films can be plotter-cut to create decals, logos and decorative displays. Nekoosa Glass Finishes® additionally offers a Bird Safety Film engineered specifically to allow birds to see windows that otherwise appear invisible.

NEKOOSA GLASS FINISHES®




Deep Etch



Light Etch




Dusted Crystal



Sand Blast





Sand Matte



 Bird Safety Film

STOCKED PRODUCTS ▶

	Finish/Color	SKU #	Liner	Size
Nekoosa Glass Finishes®				
Nekoosa Glass Finishes - Deep Etch	Opaque Frosted	DW9867-60100 ●	PET	60" x 100'
Nekoosa Glass Finishes - Light Etch	Opaque Frosted	DW4477-60100 ●	PET	60" x 100'
Nekoosa Glass Finishes - Dusted Crystal	Opaque Frosted	DW3412-60100 ●	PET	60" x 100'
Nekoosa Glass Finishes - Sand Blast	Clear Embossed	DW6231-60100 ●	PET	60" x 100'
Nekoosa Glass Finishes - Sand Matte	Opaque Frosted	DW1823-60100 ●	PET	60" x 100'
Nekoosa Glass Finishes - Bird Safety Film	DOT	 DW7154-6095 ●	PET	60" x 95'



NEKOOSA BUCKS

available in select rolls listed above.

 = PVC-Free



A NEKOOSA BRAND

Choose your perfect tape.

We recommend applying Nekoosa Glass Finishes® with these tapes.

RTape Product Number/Type		Tack Level
Application Tapes – Standard Weight Paper	4075, 4075RLA	High-Tack (16-18 oz)
Clear Film Tapes	AT65 Textured Clear Film	High Tack (2-6 oz)

TECHNICAL DATA ▶

			Deep Etch	Dusted Crystal	Light Etch
Physical Properties					
Finish			Frosted/Sandblasted Translucent Glass	Crystal Etched Translucent Glass	Acid Etched, Soft Frost Translucent Glass
Color			Clear	Clear	Clear
Adhesive			Clear, Permanent Solvent Acrylic	Clear, Permanent Solvent Acrylic	Clear, Permanent Solvent Acrylic
Film			3 mil Clear Polymeric High Grade Vinyl	4 mil Clear Polymeric High Grade Vinyl	3 mil Clear Polymeric High Grade Vinyl
Liner			3 mil Siliconized PET Liner	3 mil Siliconized PET Liner	3 mil Siliconized PET Liner
Thickness	Film	TAPPI T-411	3.0 ± 0.3 mil	4.0 ± 0.4 mil	3.0 ± 0.3 mil
	Film w/ Adhesive	TAPPI T-411	4.0 ± 0.4 mil	5.0 ± 0.5 mil	4.0 ± 0.4 mil
	Total Thickness	TAPPI T-411	7.0 ± 0.7 mil	8.0 ± 0.8 mil	7.0 ± 0.7 mil
Adhesion	Glass, 15 min Room Temp Dwell	ASTM D3330	3.0 ± 1 lb/in	3.0 ± 1 lb/in	3.0 ± 1 lb/in
	Glass, 24 hr Room Temp Dwell	ASTM D3330	5.5 ± 1 lb/in	5.5 ± 1 lb/in	5.5 ± 1 lb/in
Weight	Film w/ Adhesive	TAPPI T-410	110-132 gsm	140-170 gsm	110-132 gsm
	Total w/ Liner	TAPPI T-410	205-250 gsm	240-290 gsm	205-250 gsm
Visible Light Transmission			%	44	73
UV Light Rejection			%	66	96
Infrared Light Rejection			%	48	26
Printability			UV, Offset, Screen, Latex, Solvent, Eco-Solvent	UV, Offset, Screen, Latex, Solvent, Eco-Solvent	UV, Offset, Screen, Latex, Solvent, Eco-Solvent

			Sand Blast	Sand Matte
Physical Properties				
Finish			Translucent Sandblasted Glass	Frosted Sandblasted Glass
Color			Clear	Clear
Adhesive			Clear, Permanent Solvent Acrylic	Clear, Permanent Solvent Acrylic
Film			6 mil Clear Polymeric High Grade Vinyl	6 mil Clear Polymeric High Grade Vinyl
Liner			3 mil Siliconized PET Liner	3 mil Siliconized PET Liner
Thickness	Film	TAPPI T-411	6.0 ± 0.6 mil	6.0 ± 0.6 mil
	Film w/ Adhesive	TAPPI T-411	7.0 ± 0.7 mil	7.0 ± 0.7 mil
	Total Thickness	TAPPI T-411	10.0 ± 1.0 mil	10.0 ± 1.0 mil
Adhesion	Glass, 15 min Room Temp Dwell	ASTM D3330	3.0 ± 1 lb/in	3.0 ± 1 lb/in
	Glass, 24 hr Room Temp Dwell	ASTM D3330	5.5 ± 1 lb/in	5.5 ± 1 lb/in
Weight	Film w/ Adhesive	TAPPI T-410	220-222 gsm	220-222 gsm
	Total w/ Liner	TAPPI T-410	300-363 gsm	300-363 gsm
Visible Light Transmission			%	48
UV Light Rejection			%	90
Infrared Light Rejection			%	53
Printability			UV, Offset, Screen, Latex, Solvent, Eco-Solvent	UV, Offset, Screen, Latex, Solvent, Eco-Solvent

			Bird Safety Film
Physical Properties			
Finish			Gloss with Bird Deterrent Pattern
Color			Clear
Adhesive			Clear, Permanent Solvent Acrylic
Film			Clear PET with 1/4" Frosted Dot Pattern
Liner			2 mil PET Liner
Thickness	Film	TAPPI T-411	4.0 ± 0.4 mil
	Film w/ Adhesive	TAPPI T-411	5.0 ± 0.5 mil
	Total Thickness	TAPPI T-411	7.0 ± 0.7 mil
Adhesion	Glass, 15 min Room Temp Dwell	ASTM D3330	3.0 ± 1 lb/in
	Glass, 24 hr Room Temp Dwell	ASTM D3330	5.5 ± 1 lb/in
Weight	Film w/ Adhesive	TAPPI T-410	150-170 gsm
	Total w/ Liner	TAPPI T-410	210-250 gsm
Puncture Test			ASTM D4830 70 lbs

Conditions for Use		
Shelf Life Outdoor Durability Min Application Temp Service Temp Range Solvent Resistance Water Resistance	1 year	
	Bird Safety Film	Up to 5 years*
	Deep Etch	Up to 7 years*
	Dusted Crystal	Up to 7 years*
	Light Etch	Up to 7 years*
	Sand Blast	Up to 7 years*
	Sand Matte	Up to 7 years*
	40° F (4° C)	
-20° to 150° F (-29° to 66° C)		
Good**		
Excellent		

*Vertical applications
 **Good for most petroleum solvents and lower aliphatic alcohols.
 For ultimate solvent resistance, edge sealing is recommended.