



The clear application tape for every job, RTape Clear Choice® offers excellent transparency for easy alignment and application.

Clear Choice®

- Excellent transparency for precise alignment - perfect for beginners or pros alike!
- Effortless handling and clean removal without adhesive residue
- Compatible with wet or dry application methods
- No water whitening upon contact with water or application solution

AT60n Low Tack

Textured clear film used for transferring larger letters/graphics or protecting digital prints.

AT65 High Tack

Textured clear film for transferring small and fine detail cut graphics from vinyls with tight release liners.

AT75.1 High Tack

Easy-to-tear, textured embossed clear film creates air-egress micro channels in the adhesive for bubble-free lamination to textured or matte cut vinyl.

Applications

- Cut Lettering
- Finely Detailed Cut Graphics
- Digital Print Protection
- Overlay Graphics
- Textured Vinyl
- Matte Vinyl
- Retail Decals & Stickers
- Thermal Die-Cuts
- Films with Tight Release Liners

TECHNICAL DATA ▶

		AT60N	AT65	AT75.1
Physical Properties				
Adhesive		Acrylic/Modified Polyacrylate	Acrylic/Modified Polyacrylate	Acrylic/Modified Polyacrylate
Color		Translucent	Translucent	Translucent
Caliper	Facestock	3.7 mil (93μ)	3.7 mil (93.7μ)	4.25 mil (106.4μ)
Tack Level		Low	High	High
Die-Cut Graphic Size		Large	Small-Med	Small-Med
Compatible Vinyl		Gloss/Smooth	Gloss/Smooth	Gloss/Smooth and Matte/Textured Vinyl
Tensile		25 Mpa (3600 psi)	25 Mpa (3600 psi)	13 Mpa (2000 psi)
Elongation	PSTC-101	750%	750%	300-500%
Adhesion*		1-4 N/100 mm (1-3 oz)	2.1-6.5 N/100 mm (2-6 oz)	18-20 N/100 mm (15-18 oz)

*Adhesion to steel

Conditions for Use

Shelf Life 1 year

WARRANTY Tapes are only warranted to be free of defects in workmanship or materials at time of shipment. Nekoosa will replace or credit any material deemed to be defective. No acceptance or responsibility for loss, damage, or expense, implied or otherwise, shall be assumed by the seller or manufacturer. The end user assumes all risk and liability.

The information provided herein is correct to the best of Nekoosa's knowledge. No liability for any errors, facts or opinions are accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.